

Rec'd PCT/PTO 24 MAR 2005

Ministry of Economic  
Development



Intellectual Property Office  
of New Zealand

PCT/NZ03/00220

REC'D 15 OCT 2003

WIPO PCT

**PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)

## CERTIFICATE

This certificate is issued in support of an application for Patent registration in a country outside New Zealand pursuant to the Patents Act 1953 and the Regulations thereunder.

I hereby certify that annexed is a true copy of the Provisional Specification as filed on 30 September 2002 with an application for Letters Patent number 521694 made by CO2 PAC LIMITED.

BEST AVAILABLE COPY

Dated 1 October 2003.

**PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)

Neville Harris  
Commissioner of Patents, Trade Marks and Designs




Patents Form No. 4

Our Ref: MH504102

Patents Act 1953  
PROVISIONAL SPECIFICATION  
**HOT-FILL CONTAINER**

We, **CO2 PAC LIMITED**, a New Zealand company, of 88-90 Balmoral Road, Mt Eden, Auckland, New Zealand do hereby declare this invention to be described in the following statement:

PT0431557



## **Hot-Fill Container**

### **Background To The Invention**

5        The present invention relates to a hot-fill container which is a development of the hot-fill container described in our international application WO 02/18213 (the PCT specification), which specification is incorporated herein in its entirety where appropriate.

10        The PCT specification backgrounds the design of hot-fill containers and the problems with such designs which were overcome or at least ameliorated by the design of our PCT specification.

15        In that PCT specification a semi-rigid container was provided which had a side wall with at least one substantially vertically folding vacuum panel portion. That vacuum panel portion included an initiator portion and a control portion which resisted being expanded from the collapsed state.

20        We described in our PCT specification the inclusion of the vacuum panels at various positions along the container side wall.

25        One problem with including the vacuum panels in the upper side wall is that this can impose constraints on the overall container design. For example it makes it difficult to replicate a clear wall glass container with a hot-fill plastic container.

### **Objects of the Invention**

30        It is an object of the present invention to provide a hot-fill plastics container which is able to provide an improved option for container design while dealing with the problems inherent in hot-fill containers and/or to at least provide the public with a useful choice.

### **Summary of the Invention**

      According to one aspect of the present invention there is provided a hot-fill plastics container, a side wall of which has at least one substantially vertically folding vacuum

panel portion including a control portion which resists being expanded from the collapsed state, and wherein the said at least one vacuum panel portion is provided at or adjacent a bottom portion of said side wall so that after folding, the vacuum panel portion forms part of a base portion of the container.

Possibly, the vacuum panel portion may include an initiator portion.

Preferably the vacuum panel portion includes an upper portion which after folding of the vacuum panel portion provides a replacement container standing support.

Preferably the container as defined in the paragraph immediately above, includes a recess or instep to enable the panel portion to fold inwardly relative to the container and upwardly relative to the base portion.

According to a further aspect of this invention there is provided a hot-fill container substantially as herein described with reference to the accompanying drawings.

According to a further aspect of the invention a container forming means for a hot-fill plastics container as defined in the fifth paragraph above includes a force providing means which acts to push the base portion of the container after hot-filling to facilitate folding.

Further aspects of the invention which should be considered, in all its novel aspects will become apparent from the following description.

### **Brief Description Of Drawings**

**Figure 1:** shows very diagrammatically a cross-sectional view of a hot-fill container according to one possible embodiment of the invention in its pre-collapsed condition;

**Figure 2:** shows the bottle of Figure 1 in its collapsed position;

**Figure 3:** shows the base of Figure 1 before collapsing;

**Figure 4:** shows the base of Figure 2 following collapsing;

**Figure 5:** shows very diagrammatically an underneath view of the base of the container of Figures 1 and 2 before collapsing.

## **Description Of Possible Embodiments**

The present invention relates to hot-fill containers. Typically at a bottling plant the containers will be filled with a hot liquid and then capped before being subjected to a cold water spray resulting in the formation of a vacuum within the container which the container structure needs to be able to cope with.

As mentioned above and in our earlier PCT specification, various proposals for hot-fill container designs have been put forward.

We have further developed the hot-fill container of our PCT specification by moving the one or more vacuum panels to a bottom portion of the side wall so that following folding the vacuum panel forms part of the container base portion. This development has at least two important advantages.

Firstly, this means that there are no design features being imposed on the major portion of the side wall of the container in order to incorporate the vacuum panels. If required therefore the major portion of the side wall of the present invention could have no structural features and the container could, if required, replicate a clear wall glass container.

Secondly, by providing the vacuum panel so as to form part of the base after folding, a mechanical force could be now provided, such as by a mechanical pusher, which would engage with the container base in resetting the container shape thereby increasing the design options for an initiator portion if so required

Further, by providing the vacuum panel so as to form part of the base after folding, and a mechanical force to resetting the container shape, the initiator portion may provide further support for the latching effect of the control portion to enhance the locking of the control portion such that it will not revert to its original position.

Further, by providing the vacuum panel so as to form part of the base after folding, the container base may assume a much wider 'footprint' which enhances vertical stability of the container after it has been labelled and is released for commercial distribution.

5 Previously, the positioning of a vacuum panel at the lower portion of a side wall may have been dismissed as being unworkable in compromising vertical stability, although such an option was within the ambit of the PCT specification.

10 Still further, by providing the vacuum panel so as to form part of the base after folding, a mechanical force could be now provided, such as by a mechanical pusher, which would engage with the container base in resetting the container shape prior to the filling of the container with a suitable liquid, such that the container could be used for so called 'retort' situations, or the like, whereby the container is capped and a heating source applied. The resulting build-up of heat within the container causes a build-up of pressure  
15 also. This pressure build-up may then cause the properly calibrated control portion to revert back to its original position until the container cools again, thereby removing the internal pressure. The provision of the vacuum panel therefore reduces significantly the stress on the container sidewalls and allows advantageously less material to be used in the container construction.

20 Referring to the accompanying drawings, Figure 1 shows, by way of example only, a container in the form of a bottle. This is referenced generally by arrow 10 with a typical neck portion 12 and a side wall 9 extending to a bottom portion of 11 of the side wall and an underneath base portion 2.

25 The container 10 will typically be blow moulded from any suitable plastics material but typically this will be polyethylene tetrphalate (PET).

30 The base 2 is shown provided with plurality of reinforcing ribs 3 so as to form the typical "champagne" base although this is merely by way of example only.

35 In Figure 2 the lower side wall portion 11 is shown having folded inwardly so that a ring or annular portion 6 positioned in Figure 1 above the level of the bottom of the base 2 is now forming a new standing ring or support 6 for the container 10.

To assist this occurring and as will be seen particularly in Figures 3 and 4, immediately adjacent the ring or annular portion 6 there may be an instep or recess 8 which after folding of the bottom portion 11 enables base 2 to effectively completely disappear above the annular portion 6.

Referring now particularly to Figure 5 the base 2 with its strengthening ribs 3, is shown surrounded by the bottom portion 11 of the side wall 9. The bottom portion 11 is shown in this particular embodiment as having an initiator portion 1 which forms part of the collapsing or inverting section which yields to longitudinally directed collapsing force before the rest of the collapsing or folding section. The base 2 is shown provided within the typical base standing ring 4 which will be the first support position for the container 10 prior to vacuum removal after the inversion of the folding panel.

Associated with the initiator portion 1 is a control portion 5 which is a more steeply angled inverting section which will resist expanding from the collapsed state.

Forming the outer perimeter of the bottom portion 11 of the side wall 9 is shown the side wall standing ring or annular portion 6 which following collapsing of the panel 11 will provide the new container support.

As mentioned previously, it is envisaged that in possible embodiments of this invention the initiator portion 1 may be omitted so that in the embodiment shown in Figure 5 for example the control portion 5 would then provide essentially a continuous conical area about the base 2.

In such an embodiment, or even if an initiator portion was still provided, following the filling and capping of the bottle 10 and the use of cold water spray creating the vacuum within the filled bottle 10, a force could be imposed on the folding panel 11 such as by means of a mechanical pusher or the creation of some relative movement of the bottle base relative to a punch or the like, whereby the bottle shape was then reset to its folded or collapsed state such as shown in Figure 2.


It will be seen that by the provision of the folding portion in the bottom of the side wall 9 of the container 10 the major portion of the side wall 9 could be absent any structural features so that the container 10 could essentially replicate a glass container if this was required.

Although one particular structure for the bottom portion of the side wall 9 is shown in the accompanying drawings it will be appreciated that alternative structures could be provided. For example a plurality of folding portions could be incorporated about the base 2 in an alternative embodiment. By way of further example, the instep 8 may be recessed to such an extent that the entire lower sidewall portion and base are substantially or completely contained horizontally above the standing ring 6 even prior to folding of the vacuum panel.


Where in the foregoing description, reference has been made to specific components or integers of the invention having known equivalents then such equivalents are herein incorporated as if individually set forth.

Although this invention has been described by way of example and with reference to possible embodiments thereof, it is to be understood that modifications or improvements may be made thereto without departing from the scope or spirit of the invention.







**FIG 1**




**FIG 2**



**FIG 3**



**FIG 4**

**FIG 5**

This Page is inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record

## BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images  
problems checked, please do not report the  
problems to the IFW Image Problem Mailbox**